



1. Identification

Product identifier 40212M-CA

Product Identity Slide No-Rust

Other means of identification No-Rust ,40212M

Relevant identified uses of the substance or mixture and uses advised against

Industrial Rust Preventive

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.
430 Wheeling Road
Wheeling, IL 60090

Initial supplier identifier THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN
ADDRESS IS USED
PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY
COMPLIANT SDS FILE

Emergency
24 hour Emergency Telephone No. Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)
Customer Service: Phone: 1-847-541-7220
Fax: 1-847-541-7986

2. Hazard(s) identification

Classification of the substance or mixture

Extremely flammable gas.
Contains gas under pressure; may explode if heated.

Label elements

**Danger**

Extremely flammable gas.
Contains gas under pressure; may explode if heated.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

[Response]:

Leaking gas fire - do not extinguish unless leak can be stopped safely.
Eliminate all ignition sources if safe to do so.

[Storage]:

Store in a well ventilated place. Keep cool.
Protect from sunlight. Store in a well ventilated place.

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated light CAS Number: 0064742-47-8 Synonyms: Distillates (petroleum), hydrotreated light	30 - 60	Asp. Tox. 1;H304	----
Kerosene (petroleum) CAS Number: 0008008-20-6 Synonyms: Kerosine (petroleum)	10 - 30	Asp. Tox. 1;H304	----
Petroleum gases, liquefied CAS Number: 0068476-86-8 Synonyms: Petroleum gases, liquefied, sweetened	10 - 30	Press. Gas;H280 Flam. Gas 1;H220	----
Distillates (petroleum), solvent refined light naphthenic CAS Number: 0064741-97-5 Synonyms: Distillates (petroleum), solvent-refined light naphthenic; baseoil-unspecified	7 - 13	Not Classified	----
Sulfonic acids, petroleum, calcium salts, overbased CAS Number: 0068783-96-0 Synonyms: Sulfonic acids, petroluem, calcium salts, and overbase	7 - 13	Aquatic Chronic 4;H413	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage**Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.
See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0008008-20-6	Kerosene (petroleum)	ACGIH	TWA: 200 mg/m ³
Alberta	200 mg/m ³ TWA (as total Hydrocarbon vapour)		
British Columbia	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol expos		
Manitoba	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol expos		
New Brunswick	No Established Limit		
Newfoundland and Labrador	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol expos		
Nova Scotia	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol expos		
Northwest Territories	200 mg/m ³ TWA (as total Hydrocarbon vapour, listed under Kerosene/Jet fuels) 250 mg/m ³ STEL (as total Hydrocarbon vapour, listed under Kerosene/Jet fuels)		
Nunavut	200 mg/m ³ TWA (as total Hydrocarbon vapour, listed under Kerosene/Jet fuels) 250 mg/m ³ STEL (as total Hydrocarbon vapour, listed under Kerosene/Jet fuels)		
Ontario	200 mg/m ³ TWA (restricted to conditions where there is negligible aerosol exposure, as total hy		
Prince Edward Island	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol expos		
Quebec	No Established Limit		
Saskatchewan	200 mg/m ³ TWA (as total hydrocarbon vapour) 250 mg/m ³ STEL (as total hydrocarbon vapour)		
Yukon	No Established Limit		
0064741-97-5	Distillates (petroleum), solvent refined light naphthenic	ACGIH	No Established Limit
Alberta	No Established Limit		
British Columbia	No Established Limit		
Manitoba	No Established Limit		
New Brunswick	No Established Limit		
Newfoundland and Labrador	No Established Limit		



Safety Data Sheet SDS Revision Date: 11/02/2023
Slide No-Rust

CAS No.	Ingredient	Source	Value
Nova Scotia	No Established Limit		
Northwest Territories	No Established Limit		
Nunavut	No Established Limit		
Ontario	No Established Limit		
Prince Edward Island	No Established Limit		
Quebec	No Established Limit		
Saskatchewan	No Established Limit		
Yukon	No Established Limit		
0064742-47-8	Distillates (petroleum), hydrotreated light	ACGIH	No Established Limit
Alberta	No Established Limit		
British Columbia	200 mg/m ³ TWA (application restricted to conditions in which there are negligible aerosol expos		
Manitoba	No Established Limit		
New Brunswick	No Established Limit		
Newfoundland and Labrador	No Established Limit		
Nova Scotia	No Established Limit		
Northwest Territories	No Established Limit		
Nunavut	No Established Limit		
Ontario	No Established Limit		
Prince Edward Island	No Established Limit		
Quebec	No Established Limit		
Saskatchewan	No Established Limit		
Yukon	No Established Limit		
0068476-86-8	Petroleum gases, liquefied		
Alberta	No Established Limit		
British Columbia	No Established Limit		
Manitoba	No Established Limit		
New Brunswick	No Established Limit		



Safety Data Sheet SDS Revision Date: 11/02/2023
Slide No-Rust

CAS No.	Ingredient	Source	Value
Newfoundland and Labrador	No Established Limit		
Nova Scotia	No Established Limit		
Northwest Territories	No Established Limit		
Nunavut	No Established Limit		
Ontario	No Established Limit		
Prince Edward Island	No Established Limit		
Quebec	No Established Limit		
Saskatchewan	No Established Limit		
Yukon	No Established Limit		
0068783-96-0	Sulfonic acids, petroleum, calcium salts, overbased	ACGIH	No Established Limit
Alberta	No Established Limit		
British Columbia	No Established Limit		
Manitoba	No Established Limit		
New Brunswick	No Established Limit		
Newfoundland and Labrador	No Established Limit		
Nova Scotia	No Established Limit		
Northwest Territories	No Established Limit		
Nunavut	No Established Limit		
Ontario	No Established Limit		
Prince Edward Island	No Established Limit		
Quebec	No Established Limit		
Saskatchewan	No Established Limit		
Yukon	No Established Limit		

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 10 mg/m³ACGIH.

Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Avoid skin contact. Protective gloves recommended.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	No available information Pressurized aerosol dispensed as a mist.
Odour	No available information
Odour threshold	No available information
pH	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	No available information
Flash Point	No available information
Evaporation rate (Ether = 1)	No available information
Flammability (solid, gas)	Gas
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information Upper Explosive Limit: No available information
Vapour pressure (Pa)	No available information
Vapour Density	No available information
Relative Density	No available information
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
Oxidising properties	No available information
Explosive properties	No available information

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Safety Data Sheet SDS Revision Date: 11/02/2023
Slide No-Rust

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates (petroleum), hydrotreated light - (64742-47-8)	{calcoral}	{CalcDerm}	{CalclnhV}	{CalclnhDM}	{CalclnhG}
Kerosene (petroleum) - (8008-20-6)	{calcoral}	{CalcDerm}	{CalclnhV}	{CalclnhDM}	{CalclnhG}
Petroleum gases, liquefied - (68476-86-8)	{calcoral}	{CalcDerm}	{CalclnhV}	{CalclnhDM}	{CalclnhG}
Distillates (petroleum), solvent refined light naphthenic - (64741-97-5)	{calcoral}	{CalcDerm}	{CalclnhV}	{CalclnhDM}	{CalclnhG}
Sulfonic acids, petroleum, calcium salts, overbased - (68783-96-0)	{calcoral}	{CalcDerm}	{CalclnhV}	{CalclnhDM}	{CalclnhG}

Carcinogen Data

CAS No.	Ingredient	Source	Value
0008008-20-6	Kerosene (petroleum)	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	A3		
0064741-97-5	Distillates (petroleum), solvent refined light naphthenic	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		
0064742-47-8	Distillates (petroleum), hydrotreated light	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		
0068476-86-8	Petroleum gases, liquefied	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		
0068783-96-0	Sulfonic acids, petroleum, calcium salts, overbased	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable

Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

Treat symptomatically.

Section 12. Ecological information

Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Distillates (petroleum), hydrotreated light - (64742-47-8)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Kerosene (petroleum) - (8008-20-6)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Petroleum gases, liquefied - (68476-86-8)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Distillates (petroleum), solvent refined light naphthenic - (64741-97-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Sulfonic acids, petroleum, calcium salts, overbased - (68783-96-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.



Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1950	UN1950	UN1950
UN proper shipping name	UN1950,Aerosols	Aerosols, Flammable, (each not exceeding 1 L capacity)	Aerosols, Flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	TDG Hazard Class: 2.1;8 Sub Class: Not Applicable	IMDG: 2.1 Sub Class: Not Applicable	Air Class: 2.1 Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: Yes;

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined

Canadian Domestic Substance List (DSL):

Distillates (petroleum), hydrotreated light

Distillates (petroleum), solvent refined light naphthenic

Kerosene (petroleum)

Petroleum gases, liquefied

Sulfonic acids, petroleum, calcium salts, overbased

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Section 16. Other information

SDS Revision Date 11/02/2023

<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	2	0	G

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

End of Document