



Section 1. Identification

Product identifier 43911P-EN

Product Identity Slide Super Grease

Other means of identification Super Grease Ejector Pin Grease

Relevant identified uses of the substance or mixture and uses advised against

Industrial Ejector Pin Grease

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.
430 Wheeling Road
Wheeling, IL 60090

Initial Supplier Identifier: THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN ADDRESS IS USED
PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY COMPLIANT SDS FILE

Emergency

24 hour Emergency Telephone No. Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220
Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture

Extremely flammable gas.
Contains gas under pressure; may explode if heated.
Harmful if swallowed.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Very toxic to aquatic life with long lasting effects.

Label elements**Danger**

Extremely flammable gas.
Contains gas under pressure; may explode if heated.
Harmful if swallowed.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness and dizziness.
Very toxic to aquatic life with long lasting effects.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
Keep container tightly closed.
Avoid breathing dust, fume, gas, mist, vapours, spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves, eye protection, and face protection.

[Response]:

IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER, doctor or physician if you feel unwell.
IF SWALLOWED: Rinse mouth.
Do NOT induce vomiting.
If skin irritation occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.
Leaking gas fire - do not extinguish unless leak can be stopped safely.
In case of leakage, eliminate all ignition sources.
Collect spillage.

[Storage]:

Store in a well ventilated place. Keep container tightly closed.
Store in a well ventilated place. Keep cool.
Store locked up.
Protect from sunlight. Store in a well ventilated place.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Heptane CAS Number: 142-82-5 Synonyms: Heptane	45 - 70	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 1;H410	----
1-Decene, homopolymer, hydrogenated CAS Number: 68037-01-4 Synonyms: Dec-1-ene, homopolymer, hydrogenated	10 - 30	Asp. Tox. 1;H304	----
Petroleum gases, liquefied CAS Number: 68476-86-8 Synonyms: Petroleum gases, liquefied, sweetened	10 - 30	Press. Gas;H280 Flam. Gas 1;H220	----
Silane, dichlorodimethyl-, reaction products with silica CAS Number: 68611-44-9 Synonyms: Silane, dichlorodimethyl-, reaction products with silica	1 - 5	Not Classified	----
Poly(tetrafluoroethene) CAS Number: 9002-84-0 Synonyms: Polytetrafluoroethylene	0.5 - 1.5	Not Classified	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Skin Causes skin irritation.

Ingestion Harmful if swallowed.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area.

Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage**Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.
See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
142-82-5	Heptane	ACGIH	TWA: 400 ppm STEL: 500 ppm
		Alberta	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2050 mg/m ³ STEL
		British Columbia	400 ppm TWA 500 ppm STEL
		Manitoba	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		New Brunswick	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2050 mg/m ³ STEL
		Newfoundland and Labrador	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Nova Scotia	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Northwest Territories	400 ppm TWA 500 ppm STEL
		Nunavut	400 ppm TWA 500 ppm STEL
		Ontario	400 ppm TWA 500 ppm STEL (listed under Heptane, all isomers)
		Prince Edward Island	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Quebec	400 ppm TWAEV; 1640 mg/m ³ TWAEV 500 ppm STEV; 2050 mg/m ³ STEV
		Saskatchewan	400 ppm TWA 500 ppm STEL
		Yukon	400 ppm TWA; 1600 mg/m ³ TWA 500 ppm STEL; 2000 mg/m ³ STEL
9002-84-0	Poly(tetrafluoroethene)	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	2.5 mg/m ³ TWAEV (decomposition products; determine quantitatively the decomposition products in
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit

CAS No.	Ingredient	Source	Value
68476-86-8	Petroleum gases, liquefied	Yukon	No Established Limit
		ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
Yukon	No Established Limit		
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	Water White Pressurized aerosol dispensed as a mist.
Odour	Sweet ether Odour
Odour threshold	No available information
pH	No available information
Melting point / freezing point	205 °C 400 °F / -40 °C -40 °F
Initial boiling point and boiling range	69 °C / 156 °F
Flash Point	-7.6 °F -22 °C, Test method: (Open/Close cup)
Evapouration rate (Ether = 1)	No available information
Flammability (solid, gas)	Gas
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.2% Upper Explosive Limit: 7.7%
Vapour pressure (Pa)	No available information
Vapour Density	160 mm Hg
Relative Density	No available information
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	225 °C / 437 °F
Decomposition temperature	No available information
Viscosity (cSt)	No available information
Oxidising properties	No available information
Explosive Properties	Pressurized Container; May Burst if heated
Relative Density	0.659
Other information	No other relevant information.

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Heptane - (142-82-5)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1-Decene, homopolymer, hydrogenated - (68037-01-4)	{calcoral}	{CalcDerm}	{CalcinhV}	{CalcinhDM}	{CalcinhG}
Petroleum gases, liquefied - (68476-86-8)	{calcoral}	{CalcDerm}	{CalcinhV}	{CalcinhDM}	{CalcinhG}
Silane, dichlorodimethyl-, reaction products with silica - (68611-44-9)	{calcoral}	{CalcDerm}	{CalcinhV}	{CalcinhDM}	{CalcinhG}
Poly(tetrafluoroethene) - (9002-84-0)	{calcoral}	{CalcDerm}	{CalcinhV}	{CalcinhDM}	{CalcinhG}

Carcinogen Data

CAS No.	Ingredient	Source	Value
142-82-5	Heptane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
9002-84-0	Poly(tetrafluoroethene)	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	No Established Limit
68037-01-4	1-Decene, homopolymer, hydrogenated	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
68476-86-8	Petroleum gases, liquefied	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	4	Harmful if swallowed.
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

Possible routes of entry:

Symptoms and effects, both acute and delayed::

Treat symptomatically.

Inhalation May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Skin Causes skin irritation.

Ingestion Harmful if swallowed.

Section 12. Ecological information

Toxicity

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Heptane - (142-82-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
1-Decene, homopolymer, hydrogenated - (68037-01-4)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Petroleum gases, liquefied - (68476-86-8)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Silane, dichlorodimethyl-, reaction products with silica - (68611-44-9)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Poly(tetrafluoroethene) - (9002-84-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment



This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	1950	1950	1950
UN proper shipping name	Aerosols	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	TDG Hazard Class: 2.1 Sub Class: Not Applicable	IMDG: 2.1 Sub Class: Not Applicable	Air Class: 2.1 Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: Yes; (Heptane)

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

1-Decene, homopolymer, hydrogenated

Heptane

Petroleum gases, liquefied

Poly(tetrafluoroethene)

Silane, dichlorodimethyl-, reaction products with silica

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Section 16. Other information

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
--------------------	---	---------------------------------------	--------------------------------------	--

<u>HMIS</u>	Health Hazards 1	Flammability 4	Physical Hazards 0	Personal Protection B
--------------------	----------------------------	--------------------------	------------------------------	---------------------------------

SDS Revision Date 03/05/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H410 Very toxic to aquatic life with long lasting effects.

End of Document