



## 1. Identification

**1.1. Product identifier** 46910

**Product Identity** Slide Mold Cleaner 4  
**Alternate Names** Slide Mold Cleaner 4,  
Mixture, heptane Mold Cleaner

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** Industrial Mold Cleaner

### 1.3. Details of the supplier of the safety data sheet

**Company Name** Slide Products Inc.  
430 Wheeling Road  
Wheeling, IL 60090

#### Emergency

**24 hour Emergency Telephone No.** Emergency Telephone INFOTRAC 1-352-323-3500  
(International)  
1-800-535-5053 (North America)

**Customer Service:** Phone: 1-847-541-7220  
Fax: 1-847-541-7986

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Extremely flammable gas.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Very toxic to aquatic life.  
Very toxic to aquatic life with long lasting effects.

## 2.2. Label elements



### Danger

Extremely flammable gas.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness and dizziness.  
Very toxic to aquatic life.  
Very toxic to aquatic life with long lasting effects.

#### [Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.  
Keep container tightly closed.  
Avoid breathing dust, fume, gas, mist, vapors, spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves, eye protection, and face protection.

#### [Response]:

IF ON SKIN: Wash with plenty of soap and water.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call a POISON CENTER, doctor or physician if you feel unwell.  
Specific treatment (see information on this label).  
If skin irritation occurs: Get medical attention.  
If eye irritation persists: Get medical advice or attention.  
Take off contaminated clothing and wash before reuse.  
Leaking gas fire - do not extinguish unless leak can be stopped safely.  
Eliminate all ignition sources if safe to do so.  
Collect spillage.

**[Storage]:**

Store in a well ventilated place. Keep container tightly closed.

Store in a well ventilated place. Keep cool.

Store locked up.

Protect from sunlight. Store in a well ventilated place.

**[Disposal]:**

Dispose of contents or container in accordance with local and national regulations.

**3. Composition/information on ingredients**

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Isopropyl Alcohol CAS Number: 0000067-63-0	25 - 50	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Heptane CAS Number: 0000142-82-5	25 - 50	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	----
Petroleum gases, liquefied CAS Number: 0068476-86-8	10 - 25	Press. Gas;H280 Flam. Gas 1;H220	----

\*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

**Section 4. First aid measures**

**4.1. Description of first aid measures**

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

**Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

**Inhalation** May cause drowsiness or dizziness.

**Eyes** Causes serious eye irritation.

**Skin** Causes skin irritation.

### Section 5. Fire-fighting measures

#### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Avoid breathing dust, fume, gas, mist, vapors, spray.

#### 5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area.

Wear SCBA during clean-up immediately after fire. No smoking.

**ERG Guide No.**

----

## Section 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).  
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.  
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

## Section 7. Handling and storage

### 7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.  
Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.  
Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

### 7.3. Specific end use(s)

No available information

**Section 8. Exposure controls / personal protection**

**8.1. Control parameters**

**Exposure**

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m <sup>3</sup> ) STEL 500 ppm
ACGIH	TWA: 200 ppm STEL: 400 ppm		
NIOSH	TWA 400 ppm (980 mg/m <sup>3</sup> ) STEL: 500 ppm (1225 mg/m <sup>3</sup> )		
0000142-82-5	Heptane	OSHA	TWA 500 ppm (2000 mg/m <sup>3</sup> )
ACGIH	TWA: 400 ppm STEL: 500 ppm		
NIOSH	TWA 85 ppm (350 mg/m <sup>3</sup> ) C 440 ppm (1800 mg/m <sup>3</sup> ) [15-minute]		
0068476-86-8	Petroleum gases, liquefied	OSHA	No Established Limit
ACGIH	No Established Limit		
NIOSH	No Established Limit		

**8.2. Exposure controls**

- Respiratory**    If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes**            Protective safety glasses recommended
- Skin**             Avoid skin contact. Protective gloves recommended.
- Engineering Controls**    Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices**    Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

**Section 9. Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical State</b>	Pressurized aerosol dispensed as a mist.
<b>Color</b>	Clear
<b>Odor</b>	Characteristic
<b>Odor threshold</b>	No available information
<b>pH</b>	No available information
<b>Melting point / freezing point</b>	No available information
<b>Initial boiling point and boiling range</b>	70.6°C / 159°F
<b>Flash Point</b>	Not available
<b>Evaporation rate (Ether = 1)</b>	Faster than ether
<b>Flammability (solid, gas)</b>	Gas
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit: 1.2</b> <b>Upper Explosive Limit: 7.5</b>
<b>Vapor pressure (Pa)</b>	137 mmHg @ 20 C
<b>Vapor Density</b>	Heavier than air
<b>Relative Density</b>	0.6587
<b>Solubility in Water</b>	No available information
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Auto-ignition temperature</b>	No available information
<b>Decomposition temperature</b>	No available information
<b>Viscosity (cSt)</b>	No available information
<b>VOC Content</b>	100%
<b>Oxidising properties</b>	No available information
<b>Explosive properties</b>	No available information
<b>Water Solubility</b>	Insoluble in water

**9.2. Other information**

No other relevant information.

**Section 10. Stability and reactivity**

**10.1. Reactivity**

Hazardous Polymerization will not occur.

**10.2. Chemical stability**

Stable under normal circumstances.

**10.3. Possibility of hazardous reactions**

No available information

**10.4. Conditions to avoid**

Excessive heat and open flame.

**10.5. Incompatible materials**

Strong oxidizing agents and acids.

**10.6. Hazardous decomposition products**

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

**Section 11. Toxicological information**

**Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Isopropyl Alcohol - (67-63-0)	{calcoral}	{CalcDerm}	{CalclnhV}	{CalclnhDM}	{CalclnhG}
Heptane - (142-82-5)					





**Safety Data Sheet      SDS Revision Date: 11/06/2023**  
**Slide Mold Cleaner 4**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Petroleum gases, liquefied - (68476-86-8)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

**Carcinogen Data**

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No
NTP	Known: No; Suspected: No		
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;		
ACGIH	A4		
0000142-82-5	Heptane	OSHA	Regulated Carcinogen: No
NTP	Known: No; Suspected: No		
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
ACGIH	No Established Limit		
0068476-86-8	Petroleum gases, liquefied	OSHA	Regulated Carcinogen: No
NTP	Known: No; Suspected: No		
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
ACGIH	No Established Limit		

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

**Section 12. Ecological information**

**12.1. Toxicity**

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Isopropyl Alcohol - (67-63-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Heptane - (142-82-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Petroleum gases, liquefied - (68476-86-8)	{CalcFish}	{CalcCrust}	{CalcAlgae}

**12.2. Persistence and degradability**

There is no data available on the preparation itself.

**12.3. Bioaccumulative potential**

No available information

**12.4. Mobility in soil**

No available information

**12.5. Results of PBT and vPvB assessment**

This product contains no PBT/vPvB chemicals.

**12.6. Other adverse effects**

No available information

**Section 13. Disposal considerations**

**13.1. Waste treatment methods**

Observe all federal, state and local regulations when disposing of this substance.

**Section 14. Transport information**

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	UN1950	UN1950	UN1950
<b>14.2. UN proper shipping name</b>	UN1950,Aerosols	Aerosols, Flammable, (each not exceeding 1 L capacity) (Heptane)	Aerosols, Flammable, (each not exceeding 1 L capacity) (Heptane)
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> 2.1 <b>Sub Class:</b> Not Applicable	<b>IMDG:</b> 2.1 <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> 2.1 <b>Sub Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable

**14.5. Environmental hazards**

Marine Pollutant: Yes; ( Heptane )

**14.6. Special precautions for user**

No available information

**Section 15. Regulatory information**

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**Toxic Substance Control Act ( TSCA)** All components of this material are either listed or exempt from listing on the TSCA Inventory.

<u><b>NFPA</b></u>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	Not determined	Not determined	Not determined	Not determined

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

Isopropyl Alcohol

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



**Section 16. Other information**

**SDS Revision Date**

11/06/2023

<b>HMIS</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	1	4	0	B

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**End of Document**