

TECHNICAL DATA SHEET



Regular Silicone Mold Release Bulk/Liquid 40101PB, 40105PB, 40155PB

Product Description

Get more cycles per spray, more cycles per can, with Slide's Silicone high-quality, pure silicone-oil mold release. Keeps the most challenging parts from hanging up and stalling production. Extremely effective for investment wax casting, injection and compression molding.

Applications

Mold Release

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Silicone Mold Release

Approx. Net Weight Fill per Gal.

6 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Clear Oily Colorless Liquid

Odor

Mild, Petroleum-like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Base Type

Silicone

Evaporation Rate

Fast

HMIS Rating

2, 3, 0, X

DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

VOC % (Federal)

95

VOC g/L (Federal)

675.58

VOC lbs./Gal (Federal)

5.64

Removal

Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR)

21CFR 175.300

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 600 degrees

Working Temperature C

0 to 315 degrees

Specific Gravity

0.698

