

TECHNICAL DATA SHEET



Penetrant Plus Bulk/Liquid 41801MB, 41805MB, 41855MB

Product Description

This mono-molecular penetrating film frees rust-frozen parts. It lifts and replaces moisture with a protective film and lubricates without affecting performance of electrical equipment. Non-conductive because it has high dielectric strength and lubricates delicate electronic equipment.

Applications

Penetrating Lubricant

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Penetrating Oil

Approx. Net Weight Fill per Gal.

7 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Brownish-Tint Liquid

Odor

Petroleum like

Flash Point F

207 degrees

Flash Point C

97 degrees

Base Type

Petroleum Oil with PTFE

Evaporation Rate

Slow

HMIS Rating

1, 1, 0, Not Determined

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

88

VOC g/L (Federal)

738.13

VOC lbs./Gal (Federal)

6.16

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 338 degrees

Working Temperature C

0 to 170 degrees

Specific Gravity

0.79

