

TECHNICAL DATA SHEET





Quick Paintable Mold Release Aerosol

Product Description Quick Paintable mold release imparts a smooth, dry

film, drying quickly so you can start molding

immediately. Quick Paintable release will not interfere with part bonding, heat sealing, laminating, ultrasonic

welding or post-decorating.

Applications Mold Release

Unit Package Description 16 ounce can

Generic Description Paintable Mold Release

Net Weight Fill 11.5 net ounces

UPC Code 858799000479

Appearance Clear Oily Colorless Liquid

Odor Ether like

Flash Point F Not Applicable

Flash Point C Not Applicable

Base Type Paintable Silicone Fluid

Evaporation Rate Fast

HMIS Rating 1, 3, 0, B

DOT Proper Shipping Name UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal) 68

VOC g/L (Federal) 535.78

VOC lbs./Gal (Federal) 4.47

Removal Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR) 21CFR 178.3570

Units Per Case 12

Case Weight (lbs) 13

Working Temperature F 32 to 482 degrees

Working Temperature C 0 to 250 degrees

Propellant DME/152A

NFPA Aerosol Flammability Level 3

Independent Certifications UL recognized