


## TECHNICAL DATA SHEET



### Knock Out Mold Release Bulk/Liquid 46601PB, 46605PB, 46655PB

#### Product Description

Knock Out gets "sticky parts" cleanly out of the mold and is approved for indirect food contact. It imparts a light, dry coating that is amazingly effective, working for several cycles without re-application. Paintable formulation.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Paintable Mold Release

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mild, Petroleum-like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Propylene Glycol

#### Evaporation Rate

Fast

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

96.67

#### VOC g/L (Federal)

683.99

#### VOC lbs./Gal (Federal)

5.71

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

21CFR 178.3570

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 450 degrees

#### Working Temperature C

0 to 232 degrees

#### Specific Gravity

0.698

