

TECHNICAL DATA SHEET



DuraKote™ Mold Release Bulk/Liquid 41701PB, 41705PB, 41755PB

Product Description

DuraKote™ is a special air-drying release that will not transfer onto the molded part. It provides a dry, dust-free film on all hard-surfaced molds. It won't discolor and is paintable when it is baked on. This is a great mold release for rotational molding and acts as a semi-permanent solution when used for urethane and epoxy molding.

Applications

Mold Release

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Semi-Permanent Mold Release

Approx. Net Weight Fill per Gal.

8 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Clear Oily Colorless Liquid

Odor

Mild, Petroleum-like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Base Type

Curable Silicone Fluid

Evaporation Rate

Fast

HMIS Rating

2, 3, 0, X

DOT Proper Shipping Name

UN1993, Proper Shipping Name - Flammable Liquid, n.o.s. (Heptane, Isopropanol), Hazard Class - 3, Packing Group - II

VOC % (Federal)

99

VOC g/L (Federal)

949.03

VOC lbs./Gal (Federal)

7.92

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 600 degrees

Working Temperature C

0 to 315 degrees

Specific Gravity

0.675