

Section 1. Identification					
41112N					
D.F.L. Dry Film Lube Mold Release					
tification D.F.L. Dry Film Lube Mold Release					
substance or mixture and uses advised against					
Industrial Mold Release					
fety data sheet					
Slide Products Inc. 430 Wheeling Road Wheeling, IL 60090					
Emergency Telephone INFOTRAC 1-352-323-3500					
(International) 1-800-535-5053 (North America)					
Phone: 1-847-541-7220 Fax: 1-847-541-7986					

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.



Label elements





Danger

Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause drowsiness and dizziness. May displace oxygen and cause rapid suffocation.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Avoid breathing dust, fume, gas, mist, vapors, spray. Use only outdoors or in a well-ventilated area.

[Response]:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER, doctor or physician if you feel unwell. Leaking gas fire - do not extinguish unless leak can be stopped safely. In case of leakage, eliminate all ignition sources.

[Storage]:

Store in a well ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well ventilated place.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals. This product contains no endocrine disrupting chemicals. May displace oxygen and cause rapid suffocation.

Does not contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per US or Canadian regulations.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,1-Difluoroethane CAS Number: 75-37-6 Synonyms: 1,1-difluoroethane (HFC-152A)	45 - 55	Flammable Gas, category 1;H220 Liquified Gas;H280 Specific target organ toxicity, Single exposure category 3;H336 Simple Asphyxiant	No data available
Dimethyl ether CAS Number: 115-10-6 Synonyms: Methane, oxybis-	45 - 55	Flammable Gas, category 1;H220 Gas under pressure;H280	No data available
Fatty acids, c18-unsatd., phosphates CAS Number: 68604-99-9 Synonyms: Fatty acids, c18-unsaturated, phosphates	1 - 5		No data available
Isopropyl Alcohol CAS Number: 67-63-0 Synonyms: ISOPROPANOL, Propan-2-ol, Solvent C-3, ISOPROPYL ALCOHOL (manufacture-strong acid process	1-6	Flammable Liquid, category 2;H225 Serious eye damage / eye irritation, category 2;H319 Specific target organ toxicity, Single exposure category 3;H336	No data available

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.



Section 4. First aid measures

Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.



Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide. Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.



Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information



Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
67-63-0) Isopropyl Alcohol		400 ppm, 980 mg/m ³
		ACGIH	200 ppm 400 ppm
		NIOSH	TWA 400 ppm (980 mg/m ³) STEL: 500 ppm (1225 mg/m ³)
75-37-6	1,1-Difluoroethane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
115-10-6	Dimethyl ether	OSHA	No Established Limit
		ACGIH	TWA: 1000 ppm
		NIOSH	No Established Limit
68604-99-9	Fatty acids, c18-unsatd., phosphates	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended.

Skin Avoid skin contact. Protective gloves recommended.

Engineering
Provide adequate ventilation. Where reasonably practicable this should be
achieved by the use of local exhaust ventilation and good general extraction. If
these are not sufficient to maintain concentrations of particulates and any vapor
below occupational exposure limits suitable respiratory protection must be worn.

Other WorkUse good personal hygiene practices. Wash hands before eating, drinking,Practicessmoking or using toilet. Promptly remove soiled clothing and wash thoroughly
before reuse.

See section 2 for further details.



Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State Color Odor Melting point / freezing point Initial boiling point and boiling range Flammability (solid, gas) Upper/lower flammability or explosive limits

Flash Point Auto-ignition temperature Decomposition temperature pH Viscosity (cSt) Solubility in Water Partition coefficient n-octanol/water (Log Kow) Vapor pressure (Pa) Relative Density Vapor Density

Evaporation rate (Ether = 1) Oxidising properties Explosive properties Density

Other information

No other relevant information.

Pressurized aerosol dispensed as a mist. Milky-white Slight Alcohol <-45 °C / <-50 °F No available information Extremely flammable gas. Lower Explosive Limit:4.0% Upper Explosive Limit:25.0% Not applicable No available information No available information Not Available No available information No available information No available information No available information 1.0 (Water = 0) No available information

Extremely rapid No available information No available information Weight per gallon: 8.37



Section 10. Stability and reactivity

Reactivity Hazardous Polymerization will not occur. Chemical stability Stable under normal circumstances. Possibility of hazardous reactions No available information Conditions to avoid Excessive heat and open flame. Incompatible materials Strong oxidizing agents and acids. Hazardous decomposition products High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Safety Data Sheet D.F.L. Dry Film Lube Mold Release Safety Data Sheet SDS Revision Date: 01/22/2025

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1,1-Difluoroethane - (75-37-6)	No data available.	No data available.	No data available.	No data available.	No data available.
Dimethyl ether - (115-10-6)	No data available.	No data available.	308.00, Rat - Category: NA	No data available.	No data available.
Fatty acids, c18-unsatd., phosphates - (68604-99-9)	No data available.	No data available.	No data available.	No data available.	No data available.
Isopropyl Alcohol - (67-63-0)	5,840.00, Rat - Category: NA	16,400.00, Rabbit - Category: NA	72.60, Rat - Category: NA	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes;
		ACGIH	A4
75-37-6	1,1-Difluoroethane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit
115-10-6	Dimethyl ether	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit
68604-99-9	Fatty acids, c18-unsatd., phosphates	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable



Possible routes of entry:

No available information

Symptoms and effects, both acute and delayed:

Treat symptomatically.

Inhalation

May cause drowsiness or dizziness

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
1,1-Difluoroethane - (75-37-6)	No data available.	No data available.	No data available.
Dimethyl ether - (115-10-6)	1,783.04, Fish	755.55, Daphnia sp	154.92, Algae
Fatty acids, c18-unsatd., phosphates - (68604-99-9)	No data available.	No data available.	No data available.
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	No data available.	No data available.

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information.

Mobility in soil

No available information.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information.



Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	icao/iata			
UN number	UN1950	UN1950	UN1950			
UN proper shipping name	Aerosols	Aerosols, Flammable, (each not exceeding 1 L capacity)	Aerosols, Flammable			
Transport hazar class(es)	d DOT Hazard Class:2.1 Sub Class:Not Applicable	IMDG:2.1 Sub Class:Not Applicable	Air Class: 2.1 Sub Class: Not Applicable			
Packing group	Not Applicable	Not Applicable	Not Applicable			
Environmental hazards						
Marine Pollutant: No						
Special precautions for user						

No available information



Section 15. Regulatory information

RegulatoryThe regulatory data in Section 15 is not intended to be all-inclusive, onlyOverviewselected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000075-37-6	1,1-Difluoroethane	Yes		ACTIVE
0000115-10-6	Dimethyl ether	Yes		ACTIVE
0068604-99-9	Fatty acids, c18-unsatd., phosphates	Yes	UVCB	ACTIVE
0000067-63-0	Isopropyl Alcohol	Yes		ACTIVE

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



	Section 16. Other information						
SDS Revision Date 01/22/2025							
<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards			
	Not determined	Not determined	Not determined	Not determined			
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection			
	1	3	O	B			

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document