

ſ

Section 1. Identification				
Product identifier	41112N			
Product Identity Other means of identificati	D.F.L. Dry Film Lube Mold Release D.F.L. Dry Film Lube Mold Release			
Relevant identified uses of	the substance or mixture and uses advised against			
	Industrial Mold Release			
Details of the supplier of the supplier of the supplier of the supplication of the sup	ne safety data sheet			
Company Name	Slide Products Inc. 430 Wheeling Road Wheeling, IL 60090			
Initial Supplier Identifier:	THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN ADDRESS IS USED PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY COMPLIANT SDS FILE			
Emergency 24 hour Emergency Telephone No. Customer Service:	Emergency Telephone INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America) Phone: 1-847-541-7220 Fax: 1-847-541-7986			



Section 2. Hazard(s) identification

Classification of the substance or mixture

Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.

Label elements





Danger

Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause drowsiness and dizziness. May displace oxygen and cause rapid suffocation.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray. Use only outdoors or in a well-ventilated area.

[Response]:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER, doctor or physician if you feel unwell. Leaking gas fire - do not extinguish unless leak can be stopped safely. In case of leakage, eliminate all ignition sources.

[Storage]:

Store in a well ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well ventilated place.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1,1-Difluoroethane	45 - 55	Flam. Gas 1;H220	
CAS Number: 75-37-6		Liquified Gas;H280	
Synonyms: 1,1-difluoroethane (HFC-152A)		STOT SE 3;H336	
		Simple Asphyxiant	
Dimethyl ether	45 - 55	Flam. Gas 1;H220	
CAS Number: 115-10-6		Press. Gas;H280	
Synonyms: Methane, oxybis-			
Fatty acids, c18-unsatd., phosphates	1 - 5		
CAS Number: 68604-99-9			
Synonyms: Fatty acids, c18-unsaturated, phosphates			
Isopropyl Alcohol	1 - 6	Flam. Liq. 2;H225	
CAS Number: 67-63-0		Eye Irrit. 2;H319	
Synonyms: ISOPROPANOL, Propan-2-ol, Solvent C-3, ISOPROPYL ALCOHOL		STOT SE 3;H336	
(manufacture-strong acid process			

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]:

Specific end use(s) No available information



Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
57-63-0	Isopropyl Alcohol	ACGIH	200 ppm 400 ppm
		Alberta	200 ppm TWA; 492 mg/m ³ TWA 400 ppm STEL; 984 mg/m ³ STEL
		British Columbia	200 ppm TWA 400 ppm STEL
		Manitoba	200 ppm TWA 400 ppm STEL
		New Brunswick	400 ppm TWA; 983 mg/m ³ TWA 500 ppm STEL; 1230 mg/m ³ STEL
		Newfoundland and	200 ppm TWA 400 ppm STEL
		Labrador	
		Nova Scotia	200 ppm TWA 400 ppm STEL
		Northwest Territories	200 ppm TWA 400 ppm STEL
		Nunavut	200 ppm TWA 400 ppm STEL
		Ontario	200 ppm TWA 400 ppm STEL
		Prince Edward Island	200 ppm TWA 400 ppm STEL
		Quebec	400 ppm TWAEV; 985 mg/m ³ TWAEV 500 ppm STEV; 1230 mg/m ³
			STEV
		Saskatchewan	200 ppm TWA 400 ppm STEL
		Yukon	400 ppm TWA; 980 mg/m ³ TWA 500 ppm STEL; 1225 mg/m ³ STEL
5-37-6	1,1-Difluoroethane	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
15-10-6	Dimethyl ether	ACGIH	TWA: 1000 ppm
		Alberta	No Established Limit
		British Columbia	1000 ppm TWA
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario Prince Edward Island	No Established Limit No Established Limit
		Quebec	
			No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit



Safety Data Sheet SDS Revision Date: 01/22/2025 D.F.L. Dry Film Lube Mold Release

CAS No.	Ingredient	Source	Value
68604-99-9	Fatty acids, c18-unsatd.,	ACGIH	No Established Limit
	phosphates	Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Exposure controls

- **Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- **Eyes** Protective safety glasses recommended.
- Skin Avoid skin contact. Protective gloves recommended.
- Engineering
 Provide adequate ventilation. Where reasonably practicable this should be
 achieved by the use of local exhaust ventilation and good general extraction. If
 these are not sufficient to maintain concentrations of particulates and any vapour
 below occupational exposure limits suitable respiratory protection must be worn.
- Other WorkUse good personal hygiene practices. Wash hands before eating, drinking,Practicessmoking or using toilet. Promptly remove soiled clothing and wash thoroughly
before reuse.

See section 2 for further details.



Safety Data Sheet SDS Revision Date: 01/22/2025 D.F.L. Dry Film Lube Mold Release

Section 9. Physical and chemical properties

Appearance

Odour Odour threshold pH Melting point / freezing point Initial boiling point and boiling range Flash Point Evapouration rate (Ether = 1) Flammability (solid, gas) Upper/lower flammability or explosive limits

Vapour pressure (Pa) Vapour Density Relative Density Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature Decomposition temperature Viscosity (cSt) Oxidising properties Explosive properties Density

Other information

No other relevant information.

Milky-white Pressurized aerosol dispensed as a mist. Slight Alcohol No available information Not Available <-45 °C / <-50 °F No available information Not applicable Extremely rapid Extremely flammable gas. **Lower Explosive Limit:** 4.0%

Upper Explosive Limit: 25.0%

No available information No available information 1.0 (Water = 0) No available information No available information

No available information No available information No available information No available information No available information Weight per gallon: 8.37



Section 10. Stability and reactivity

Reactivity Hazardous Polymerization will not occur. Chemical stability Stable under normal circumstances. Possibility of hazardous reactions No available information Conditions to avoid Excessive heat and open flame. Incompatible materials Strong oxidizing agents and acids. Hazardous decomposition products High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Safety Data SheetSDS Revision Date: 01/22/2025D.F.L. Dry Film Lube Mold Release

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1,1-Difluoroethane - (75-37-6)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Dimethyl ether - (115-10-6)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Fatty acids, c18-unsatd., phosphates - (68604-99-9)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
lsopropyl Alcohol - (67-63-0)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

Carcinogen Data

CAS No.	Ingredient	Source	Value		
67-63-0	Isopropyl Alcohol	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;		
		ACGIH	A4		
75-37-6	1,1-Difluoroethane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
115-10-6	Dimethyl ether	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		
68604-99-9	Fatty acids, c18-unsatd., phosphates	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
		ACGIH	No Established Limit		

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

No available information

Symptoms and effects, both acute and delayed:

Treat symptomatically.

Inhalation

May cause drowsiness or dizziness.



Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
1,1-Difluoroethane - (75-37-6)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Dimethyl ether - (115-10-6)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Fatty acids, c18-unsatd., phosphates - (68604-99-9)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Isopropyl Alcohol - (67-63-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability There is no data available on the preparation itself. Bioaccumulative potential No available information Mobility in soil No available information Results of PBT and vPvB assessment This product contains no PBT/vPvB/vPvM chemicals. Other adverse effects No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	icao/iata			
UN number	UN1950	UN1950	UN1950			
UN proper shipping name	Aerosols	Aerosols, Flammable, (each not exceeding 1 L capacity)	Aerosols, flammable			
Transport hazaro class(es)	d TDG Hazard Class:Not Applicable Sub Class:Not Applicable	IMDG:2.1 Sub Class:Not Applicable	Air Class: 2.1 Sub Class: Not Applicable			
Packing group	Not Applicable	Not Applicable	Not Applicable			
Environmental hazards						
Marine Pollutant: No;						
Special precautions for user						

No available information



Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

1,1-Difluoroethane

Dimethyl ether

Fatty acids, c18-unsatd., phosphates

Isopropyl Alcohol

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



	Section 16. Other information					
SDS Revision Date 01/22/2025						
<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards		
	Not determined	Not determined	Not determined	Not determined		
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection		
	1	3	O	B		

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document