

Section	1.	Identification
---------	----	----------------

Product identifier

Product Identity Other means of identification 42112N

SSL Mold Release SSL Mold Release

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Release

Details of the supplier of the safety data sheet

Company Name

Slide Products Inc. 430 Wheeling Road Wheeling, IL 60090

Emergency	
24 hour Emergency Telephone	Emergency Telephone INFOTRAC 1-352-323-3500
No.	(International)
	1-800-535-5053 (North America)
Customer Service:	Phone: 1-847-541-7220
	Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture

Flam. Gas 1;H220	Extremely flammable gas.
Flam. Aerosol 2;H223	Flammable aerosol.
H229	Pressurized container: May burst if heated.
Press. Gas;H280	Contains gas under pressure; may explode if heated.
{PCField5d}	May cause drowsiness or dizziness.
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.



Safety Data Sheet SSL Mold Release

Label elements





Danger

H220 Extremely flammable gas.
H223 Flammable aerosol.
H229 Pressurized container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H336 May cause drowsiness and dizziness.
May displace oxygen and cause rapid suffocation.

[Prevention]:

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P271 Use only outdoors or in a well-ventilated area.

[Response]:

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER, doctor or physician if you feel unwell.
P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.
P381 In case of leakage, eliminate all ignition sources.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed. P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F. [Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the NOM-018-STPS-2015 Regulation.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Dimethyl ether CAS Number: 115-10-6	55 - 65	Flam. Gas 1;H220 Press. Gas;H280	
1,1-Difluoroethane CAS Number: 75-37-6	20 - 40	Flam. Gas 1;H220 Liquified Gas;H280 STOT SE 3;H336 Simple Asphyxiant	
Dimethylsiloxane CAS Number: 63148-62-9	1 - 10	Not Classified	

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]:

Specific end use(s)

No available information



Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
75-37-6	1,1-Difluoroethane	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit
115-10-6	Dimethyl ether	ACGIH	TWA: 1000 ppm
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit
63148-62-9	Dimethylsiloxane	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended.

Skin Avoid skin contact. Protective gloves recommended.

Engineering
 Provide adequate ventilation. Where reasonably practicable this should be
 achieved by the use of local exhaust ventilation and good general extraction. If
 these are not sufficient to maintain concentrations of particulates and any vapour
 below occupational exposure limits suitable respiratory protection must be worn.

Other WorkUse good personal hygiene practices. Wash hands before eating, drinking,Practicessmoking or using toilet. Promptly remove soiled clothing and wash thoroughly
before reuse.

See section 2 for further details.



Section 9. Physical and chemical properties

Appearance	Colorless Pressurized aerosol dispensed as a mist.
Odour	No Odour
Odour threshold	N/A
рН	No available information
Melting point / freezing point	< -45 °C/ <-50 °F
Initial boiling point and boiling range	No available information
Flash Point	Not applicable
Evapouration rate (Ether = 1)	No available information
Flammability (solid, gas)	Extremely flammable gas.
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information
	Upper Explosive Limit: No available information
Vapour pressure (Pa)	No available information
Vapour Density	No available information
Relative Density	0.81 (Water = 1)
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log	No available information
Kow)	
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
Oxidising properties	No available information
Explosive properties	No available information
Density	Weight per gallon: 6.79

Other information No other relevant information.



Section 10. Stability and reactivity

Reactivity Hazardous Polymerization will not occur. Chemical stability Stable under normal circumstances. Possibility of hazardous reactions No available information Conditions to avoid Excessive heat and open flame. Incompatible materials Strong oxidizing agents and acids. Hazardous decomposition products High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Safety Data Sheet SDS Revision Date: 01/23/2025 SSL Mold Release

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Dimethyl ether - (115-10-6)	No data available.	No data available.	308.00, Rat - Category: NA	No data available.	No data available.
1,1-Difluoroethane - (75-37- 6)	No data available.	No data available.	No data available.	No data available.	No data available.
Dimethylsiloxane - (63148- 62-9)	17,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value	
75-37-6	1,1-Difluoroethane	IARC	roup 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Established Limit	
115-10-6	Dimethyl ether	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Established Limit	
63148-62-9	Dimethylsiloxane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
		ACGIH	No Established Limit	

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

No available information

Symptoms and effects, both acute and delayed:

Treat symptomatically.

Inhalation

May cause drowsiness or dizziness



Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Dimethyl ether - (115-10-6)	1,783.04, Fish	755.55, Daphnia sp	154.92, Algae
1,1-Difluoroethane - (75-37-6)	No data available.	No data available.	No data available.
Dimethylsiloxane - (63148-62-9)	>2,000.00, Fish	>2,000.00, Daphnia magna	>2,000.00, Algae

Persistence and degradability

There is no data available on the preparation itself. **Bioaccumulative potential** No available information **Mobility in soil** No available information **Results of PBT and vPvB assessment** This product contains no PBT/vPvB/vPvM chemicals. **Other adverse effects** No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	SCT (Domestic Surface	IMO / IMDG (Ocean	icao/iata
	Transportation)	Transportation)	
UN number	UN1950	UN1950	UN1950
UN proper	Aerosols	Aerosols, Flammable, (each not	Aerosols,
shipping name		exceeding 1 L capacity)	flammable
Transport hazar	d DOT Hazard Class:Not	IMDG:2.1	Air Class:2.1
class(es)	Applicable	Sub Class:Not Applicable	Sub Class:Not
	Sub Class:Not Applicable		Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: No; Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria of NOM-018-STPS-2015 and the SDS contains the information required by those regulations.

Mexico - National Inventory of Chemical Substances (INSQ):

1,1-Difluoroethane

Dimethyl ether

Dimethylsiloxane



1

Section 16. Other information				
SDS Revision Date 01/23/2025				
<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection

0

В

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

3

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document