



**Section 1. Identification**

**Product identifier** 442BULK

**Product Identity** Bulk On/Cycle Mold Cleaner

**Other means of identification** Bulk On/Cycle Mold Cleaner  
( SDS applies to pint, 1G, 5G, and 55G sizes )

**Relevant identified uses of the substance or mixture and uses advised against**

Industrial Mold Cleaner

**Details of the supplier of the safety data sheet**

**Company Name** Slide Products Inc.  
430 Wheeling Road  
Wheeling, IL 60090

**Emergency**

**24 hour Emergency Telephone No.** Emergency Telephone INFOTRAC 1-352-323-3500  
(International)  
1-800-535-5053 (North America)

**Customer Service:** Phone: 1-847-541-7220  
Fax: 1-847-541-7986

**Section 2. Hazard(s) identification**

**Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

**Label elements****Warning**

Flammable liquid and vapor.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness and dizziness.

**[Prevention]:**

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.  
Keep container tightly closed.  
Keep cool.  
Ground, bond container and receiving equipment.  
Use explosion-proof electrical, ventilating, light, equipment.  
Use only non-sparking tools.  
Take action to prevent static discharges.  
Do not breathe dust, fume, mist, vapors or spray.  
Avoid breathing dust, fume, gas, mist, vapors, spray.  
Do not get in eyes, on skin, or on clothing.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves, eye protection, and face protection.

**[Response]:**

IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.  
IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call a POISON CENTER, doctor or physician if you feel unwell.  
Do NOT induce vomiting.  
If skin irritation or a rash occurs: Get medical advice or attention.  
If eye irritation persists: Get medical advice or attention.  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

**[Storage]:**

Store in a well ventilated place. Keep container tightly closed.  
Store in a well ventilated place. Keep cool.  
Store locked up.



**[Disposal]:**

Dispose of contents or container in accordance with local and national regulations.

**Other hazards**

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

**Section 3. Composition/information on ingredients**

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
D'limonene, citrus, ext. CAS Number: 94266-47-4 Synonyms: D'limonene, citrus, ext.	30-60	Flammable Liquid, category 3;H226 Aspiration hazard, category 1;H304 Skin corrosion/irritation category 2;H315 Skin sensitizer category 1;H317 Aquatic toxicity (acute), category 1;H400 Aquatic toxicity (chronic), category 1;H410	No data available
Isopropyl Alcohol CAS Number: 67-63-0 Synonyms: ISOPROPANOL, Propan-2-ol, Solvent C-3, ISOPROPYL ALCOHOL (manufacture-strong acid process)	20-40	Flammable Liquid, category 2;H225 Serious eye damage / eye irritation, category 2;H319 Specific target organ toxicity, Specific exposure category 3;H336	No data available
Hydrocarbon Solvent CAS Number: 64742-48-9 Synonyms: Hydrotreated heavy naphtha (petroleum), Naphtha (petroleum), hydrotreated heavy	20-40	Aspiration hazard, category 1;H304	No data available

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

**Section 4. First aid measures**

**Description of first aid measures**

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

**Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed****Overview POTENTIAL HEALTH EFFECTS**

**Eye Contact:** May cause tearing, stinging, redness, irritation, and burns.

**Inhalation:** Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

**Ingestion:** Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

**Skin Contact:** Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

**Signs And Symptoms Of Exposure:** Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Eyes** Causes serious eye irritation.  
**Skin** May cause an allergic skin reaction. Causes skin irritation.

**Section 5. Fire-fighting measures**

**Extinguishing media**

Use dry chemicals, carbon dioxide foam, water fog, or inert gas (nitrogen) for small fires. For large fires use foam, water fog, or water spray. Water fog and spray are effective in cooling containers and adjacent structures but might cause frothing and/or not achieve extinguishment. A water jet may be used to cool the container's external walls to prevent pressure build-up, auto ignition, or explosion. NEVER use a water jet directly on the fire. Product will float and can be re-ignited on surface of water.

**Special hazards arising from the substance or mixture**

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapors or spray.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Do not get in eyes, on skin, or on clothing.

**Advice for fire-fighters**

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

**ERG Guide No.**

128

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).  
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### Environmental precautions

Do not allow spills to enter drains or waterways.

### Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.  
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. Eliminate ignition sources. Soak up with noncombustible absorbent material. Remove absorbent material for proper disposal.

## Section 7. Handling and storage

### Precautions for safe handling

Handle containers carefully to prevent damage and spillage.  
See section 2 for further details. - [Prevention]:

### Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong acids, alkalis, and oxidizers such as liquid chlorine, halogens, hydrogen peroxide, oxygen.

**Other Precautions:**All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Empty containers may contain material residues which can ignite with explosive force. Cutting or welding of empty containers can cause fire, explosion, or release fumes from residues. Keep containers closed and drum bungs in place. Dispose of in a licensed facility.  
See section 2 for further details. - [Storage]:

### Specific end use(s)

No available information

**Section 8. Exposure controls / personal protection**

**Control parameters**

**Exposure**

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	OSHA	400 ppm, 980 mg/m <sup>3</sup>
		ACGIH	200 ppm 400 ppm
		NIOSH	TWA 400 ppm (980 mg/m <sup>3</sup> ) STEL: 500 ppm (1225 mg/m <sup>3</sup> )
64742-48-9	Hydrocarbon Solvent	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
94266-47-4	D'limonene, citrus, ext.	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

**Exposure controls**

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

**Eyes** Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

**Skin** Avoid skin contact. Wear nitrile or similar chemical resistant gloves to keep skin contact to a minimum.  
Refer to the manufacturer's recommendations regarding the suitability of any gloves used.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

**Section 9. Physical and chemical properties**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid
<b>Color</b>	Clear
<b>Odor</b>	Sweet
<b>Melting point / freezing point</b>	No available information
<b>Initial boiling point and boiling range</b>	177.8°C / 352°F
<b>Flammability (solid, gas)</b>	No available information
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 0.7% <b>Upper Explosive Limit:</b> 7.0%
<b>Flash Point</b>	50°C / 122°F (Closed Cup)
<b>Auto-ignition temperature</b>	No available information
<b>Decomposition temperature</b>	No available information
<b>pH</b>	No available information
<b>Viscosity (cSt)</b>	No available information
<b>Solubility in Water</b>	Slight
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Vapor pressure (Pa)</b>	1 mm Hg @ 21°C (70°F)
<b>Relative Density</b>	0.841 (Water=1)
<b>Vapor Density</b>	4.7 (Air=1)
<b>Evaporation rate (Ether = 1)</b>	Slow Minutes
<b>VOC Content</b>	780 gm/L
<b>Oxidising properties</b>	No available information
<b>Explosive properties</b>	No available information

**Other information**

No other relevant information.



## Section 10. Stability and reactivity

### Reactivity

Hazardous Polymerization will not occur.

### Chemical stability

Stable under normal circumstances.

### Possibility of hazardous reactions

No available information.

### Conditions to avoid

Excessive heat and open flame.

### Incompatible materials

Strong acids, alkalis, and oxidizers such as liquid chlorine, halogens, hydrogen peroxide, oxygen.

### Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

## Section 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



**Safety Data Sheet**  
**Bulk On/Cycle Mold Cleaner**

**SDS Revision Date: 11/19/2024**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
D'limonene, citrus, ext. – (94266-47-4)	No data available.	No data available.	No data available.	No data available.	No data available.
Isopropyl Alcohol – (67-63-0)	5,840.00, Rat - Category: NA	16,400.00, Rabbit - Category: NA	72.60, Rat - Category: NA	No data available.	No data available.
Hydrocarbon Solvent – (64742-48-9)	> 5,000.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.

**Carcinogen Data**

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes;
		ACGIH	A4
64742-48-9	Hydrocarbon Solvent	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit
94266-47-4	D'limonene, citrus, ext.	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable



Possible routes of entry:

**Symptoms and effects, both acute and delayed::**

#### **POTENTIAL HEALTH EFFECTS**

**Eye Contact:** May cause tearing, stinging, redness, irritation, and burns.

**Inhalation:** Irritating to respiratory tract. Prolonged or repeated breathing of very high vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

**Ingestion:** Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

**Skin Contact:** Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

**Signs And Symptoms Of Exposure:** Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys. Treat symptomatically.

**Eyes** Causes serious eye irritation.

**Skin** May cause an allergic skin reaction. Causes skin irritation.

**Section 12. Ecological information**

**Toxicity**

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
D'limonene, citrus, ext. - (94266-47-4)	No data available.	No data available.	No data available.
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	No data available.	No data available.
Hydrocarbon Solvent - (64742-48-9)	18.00, Oncorhynchus mykiss	4.50, Daphnia magna	3.10, Pseudokirchneriella subcapitata

**Persistence and degradability**

There is no data available on the preparation itself.

**Bioaccumulative potential**

No available information

**Mobility in soil**

No available information

**Results of PBT and vPvB assessment**

This product contains no PBT/vPvB/vPvM chemicals.

**Other adverse effects**

No available information

**Section 13. Disposal considerations**

**Waste treatment methods**

Observe all federal, provincial and local regulations when disposing of this substance.

**Section 14. Transport information**

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>UN number</b>	NA1993	UN1993	UN1993
<b>UN proper shipping name</b>	Combustible liquid, n.o.s. (Isopropanol)	Flammable liquids, n.o.s., (Isopropanol)	Flammable liquids, n.o.s., (Isopropanol)
<b>Transport hazard class(es)</b>	<b>DOT Hazard Class:3</b> <b>Sub Class:Not Applicable</b>	<b>IMDG:3</b> <b>Sub Class:Not Applicable</b>	<b>Air Class:3</b> <b>Sub Class:Not Applicable</b>
<b>Packing group</b>	III	III	III

**Environmental hazards**

Marine Pollutant: Yes; ( D'limonene, citrus, ext. )

**Special precautions for user**

No available information.

**Section 15. Regulatory information**

**Regulatory Overview**      The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA’s Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

**Toxic Substance Control Act (TSCA)**

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0094266-47-4	D’limonene, citrus, ext.	No		
0064742-48-9	Hydrocarbon Solvent	Yes	UVCB	ACTIVE
0000067-63-0	Isopropyl Alcohol	Yes		ACTIVE

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



**Section 16. Other information**

**SDS Revision Date** 11/19/2024

<b><u>NFPA</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	Not determined	Not determined	Not determined	Not determined

<b><u>HMIS</u></b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	1	2	0	G

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products.

Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness and dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

**End of Document**