

Section 1. Identification

Product identifier 457CONC

Product Identity

Slide Pure Eze Mold Release 100% Oil

Other means of identification

Slide Pure Eze Mold Release 100% Oil

(SDS applies to pint, 1G, 5G, and 55G sizes)

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Release Oil

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.

430 Wheeling Road Wheeling, IL 60090

Emergency

24 hour Emergency Telephone

Emergency Telephone INFOTRAC 1-352-323-3500

No.

(International)

1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220

Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

The substance is not classified according to the OSHA Hazcom or WHMIS regulations.



Label elements

The substance is not classified according to the OSHA Hazcom or WHMIS regulations.



[Prevention]:

No GHS prevention statements

[Response]:

No GHS response statements

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

Other hazards

This product contains no PBT/vPvB chemicals.

This product contains no endocrine disrupting chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
White mineral oil (petroleum)	100	Not Classified	
CAS Number: 8042-47-5			No data available
Synonyms: White mineral oil (petroleum)			140 data available

The actual concentration or concentration range is withheld as a trade secret.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.



Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.



Safety Data Sheet Slide Pure Eze Mold Release 100% Oil

Section 7. Handling and storage

SDS Revision Date: 10/30/2024

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
8042-47-5	White mineral oil (petroleum)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use

the appropriate, certified respirators.

Eyes Protective safety glasses recommended.

Skin Avoid skin contact. Protective gloves recommended.

Engineering Provide adequate ventilation. Where reasonably practicable this should be

Controls achieved by the use of local exhaust ventilation and good general extraction. If

these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking,

Practices smoking or using toilet. Promptly remove soiled clothing and wash thoroughly

before reuse.

See section 2 for further details.



Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State Liquid Color Clear

Odor Not Available <-28.9 °C / <-20 °F Melting point / freezing point Initial boiling point and boiling range No available information Flammability (solid, gas) No available information

Upper/lower flammability or explosive limits Lower Explosive Limit: No available information

Upper Explosive Limit: No available

information

190 °C / 374 °F **Flash Point**

Auto-ignition temperature No available information **Decomposition temperature** No available information рΗ No available information Viscosity (cSt) No available information **Solubility in Water** No available information No available information

Partition coefficient n-octanol/water (Log

Kow)

Vapor pressure (Pa) Nil

Relative Density .871 (Water = 1)

No available information Vapor Density

No available information **Evaporation rate (Ether = 1) Oxidizing properties** No available information **Explosive properties** No available information

Other information

No other relevant information.



Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information.

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
White mineral oil	> 5,000.00, Rat -	No data	No data	No data	No data
(petroleum) - (8042-47-5)	Category: NA	available.	available.	available.	available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
8042-47-5	White mineral oil	OSHA	Regulated Carcinogen: No;
	(petroleum)	NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3:
			No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

Treat symptomatically.



Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
White mineral oil (petroleum) - (8042-47-5)	101.00, Oncorhynchus mykiss	101.00, Daphnia magna	101.00, Pseudokirchneriella subcapitata
	, , , , , , , , , , , , , , , , , , , ,	, , , , , , , , , , , , , , , , , , ,	, , , , , , , , , , , , , , , , , , , ,

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information.

Mobility in soil

No available information.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
Transport hazard class(es)	DOT Hazard Class:Not Applicable Sub Class:Not Applicable	IMDG:Not Applicable Sub Class:Not Applicable	Air Class:Not Applicable Sub Class:Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: No;

Special precautions for user

No available information



Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0008042-47-5	White mineral oil (petroleum)	Yes	UVCB	ACTIVE

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



	•	
Section 16	5. Other	information

SDS Revision Date 10/30/2024

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

Not Applicable

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document