

Section 1. Identification					
Product identifier	46710P				
Product Identity Other means of identification					
Relevant identified uses of the s	substance or mixture and uses advised against				
	Industrial Rust Preventive				
Details of the supplier of the saf	ety data sheet				
Company Name	Impany NameSlide Products Inc.430 Wheeling RoadWheeling, IL 60090				
Emergency 24 hour Emergency Telephone No.	Emergency Telephone INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)				
ustomer Service: Phone: 1-847-541-7220 Fax: 1-847-541-7986					
	ection 2. Hazard(s) identification				

# Classification of the substance or mixture

Flam. Gas 1;H220	Extremely flammable gas.
Skin Irrit. 2;H315	Causes skin irritation.
{PCField5d}	May cause drowsiness or dizziness.
Aquatic Chronic 1;H410	Very toxic to aquatic life with long lasting effects.



Label elements



Danger

H220 Extremely flammable gas.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H410 Very toxic to aquatic life with long lasting effects.

# [Prevention]:

P210 Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

# [Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P332+313 If skin irritation occurs: Get medical attention.

P362+364 Take off contaminated clothing and wash it before reuse.

P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.

P381 In case of leakage, eliminate all ignition sources.

P391 Collect spillage.

# [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

# [Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the NOM-018-STPS-2015 Regulation.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Heptane CAS Number: 142-82-5	45 - 55	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 1;H410	
White mineral oil (petroleum) CAS Number: 8042-47-5	12 - 18	Not Classified	
Petroleum gases, liquefied CAS Number: 68476-86-8	8 - 18	Press. Gas;H280 Flam. Gas 1;H220	
Calcium carbonate CAS Number: 471-34-1	8 - 15	Not Classified	
Lecithins, polymers with glycerol, oiticica oil, phthalic anhydride and soybean oil CAS Number: 68910-52-1	5 - 10		

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

#### Section 4. First aid measures

#### Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



# Most important symptoms and effects, both acute and delayed

**Overview** No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

> Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Skin** Causes skin irritation.

# Section 5. Fire-fighting measures

# Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

#### Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide. Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.

# Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

#### ERG Guide No.



# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### **Environmental precautions**

Do not allow spills to enter drains or waterways.

#### Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

# Section 7. Handling and storage

#### Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

#### Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]:

# Specific end use(s)

No available information



# Section 8. Exposure controls / personal protection

# **Control parameters**

CAS No.	Ingredient	Source	Value
142-82-5	Heptane	ACGIH	400 ppm 500 ppm
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	400 ppm TWA VLE-PPT; 1600 mg/m <sup>3</sup> TWA VLE-PPT 500 ppm
			STEL [PPT-CT]
471-34-1	Calcium carbonate	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit
8042-47-5	White mineral oil (petroleum)	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit
68476-86-8	Petroleum gases, liquefied	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit
68910-52-1	Lecithins, polymers with glycerol,	ACGIH	No Established Limit
	oiticica oil, phthalic anhydride and	DNEL Local Exposure	No Established Limit
	soybean oil	DNEL Systematic Exposure	No Established Limit
		National	No Established Limit

# **Exposure Limits**

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup>OSHA PEL and 5 mg/m<sup>3</sup>ACGIH.

# Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended.
Skin	Avoid skin contact. Protective gloves recommended.
Engineering	Provide adequate ventilation. Where reasonably practicable this should be
Controls	achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.



Section 9. Physical and chemical properties

Appearance Odour **Odour threshold** pН Melting point / freezing point Initial boiling point and boiling range **Flash Point** Evapouration rate (Ether = 1) Flammability (solid, gas) Upper/lower flammability or explosive limits Vapour pressure (Pa) Vapour Density **Relative Density** Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature **Decomposition temperature** Viscosity (cSt) **Oxidising properties Explosive properties** Water Solubility **Bulk Density** 

Tan Pressurized aerosol dispensed as a mist. Fetid Odour No available information No available information <-40°C / <-40°F 39-40°C / 103-104°F Flammable aerosol Fast Flam. Gas 1;H220 Extremely flammable gas. Lower Explosive Limit: 1.2% **Upper Explosive Limit:** 7.5% 137 mm Hg >1 (Air=1) 0.644 (Water = 1) No available information Nil 5.671 lb/gal @ 60°F

**Other information** No other relevant information.



Section 10. Stability and reactivity

# Reactivity Hazardous Polymerization will not occur. Chemical stability Stable under normal circumstances. Possibility of hazardous reactions No available information Conditions to avoid Excessive heat and open flame. Incompatible materials Strong oxidizing agents and acids. Hazardous decomposition products High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

# Section 11. Toxicological information

# Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



# Safety Data Sheet SDS Revision Date: 03/05/2025 Slide White Rhino Rust Preventive

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Heptane - (142-82-5)	17,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	103.00, Rat - Category: NA	No data available.	No data available.
White mineral oil (petroleum) - (8042-47-5)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.
Petroleum gases, liquefied - (68476-86-8)	No data available.	No data available.	No data available.	No data available.	No data available.
Calcium carbonate - (471-34-1)	>2,000.00, Rat - Category: 5	>2,000.00, Rat - Category: 5	No data available.	No data available.	No data available.
Lecithins, polymers with glycerol, oiticica oil, phthalic anhydride and soybean oil - (68910-52-1)	No data available.	No data available.	No data available.	No data available.	No data available.

# Carcinogen Data

CAS No.	Ingredient	Source	Value
142-82-5	Heptane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
			Group 4: No;
		ACGIH	No Established Limit
471-34-1	Calcium carbonate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
			Group 4: No;
		ACGIH	No Established Limit
8042-47-5	White mineral oil (petroleum)	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
			Group 4: No;
		ACGIH	No Established Limit
68476-86-	Petroleum gases, liquefied	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
8			Group 4: No;
		ACGIH	No Established Limit
68910-52-	Lecithins, polymers with glycerol, oiticica oil, phthalic anhydride	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
1	and soybean oil		Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable



#### Slide White Rhino Rust Preventive

Possible routes of entry: No available information Symptoms and effects, both acute and delayed: No chronic toxicity or long term toxicity information available. Treat symptomatically. Inhalation May cause drowsiness or dizziness Skin Causes skin irritation

# Section 12. Ecological information

# Toxicity

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity** 

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Heptane - (142-82-5)	375.00, Oreochromis mossambicus	3.90, Daphnia magna	4.34, Pseudokirchneriella subcapitata
White mineral oil (petroleum) - (8042-47-5)	101.00, Oncorhynchus mykiss	101.00, Daphnia magna	101.00, Pseudokirchneriella subcapitata
Petroleum gases, liquefied - (68476-86-8)	No data available.	No data available.	No data available.
Calcium carbonate - (471-34-1)	101.00, Oncorhynchus mykiss	101.00, Daphnia magna	No data available.
Lecithins, polymers with glycerol, oiticica oil, phthalic anhydride and soybean oil - (68910-52-1)	No data available.	No data available.	No data available.

# Persistence and degradability

There is no data available on the preparation itself. **Bioaccumulative potential** No available information Mobility in soil No available information **Results of PBT and vPvB assessment** This product contains no PBT/vPvB/vPvM chemicals. Other adverse effects No available information



# Section 13. Disposal considerations

#### Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

# Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	SCT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	icao/iata			
UN number	UN1950	UN1950	UN1950			
UN proper shipping name	Aerosols	Aerosols, flammable	Aerosols, flammable			
Transport hazard class(es)	Class:2.1 Sub Class:Not Applicable	Class:2.1 Sub Class:Not Applicable	Class:2.1 Sub Class:Not Applicable			
Packing group	Not Applicable	Not Applicable	Not Applicable			
Environmental ha	zards					
Marine Pollutant: Yes; (Heptane)						
Special precautions for user						

No available information



# Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria of NOM-018-STPS-2015 and the SDS contains the information required by those regulations.

# Mexico - National Inventory of Chemical Substances (INSQ):

Calcium carbonate

Heptane

Petroleum gases, liquefied

White mineral oil (petroleum)



Section 16. Other information					
SDS Revision Date 03/05/2025					
<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards	
	Not determined	Not determined	Not determined	Not determined	
<u>HMIS</u>	Health Hazards	Flammability	<b>Physical Hazards</b>	<b>Personal Protection</b>	
	1	4	0	B	

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

# End of Document