

Section 1. Identification

Product identifier 47410

Product Identity X-EMPT VOC-Exempt Mold Cleaner
Other means of identification X-EMPT VOC-Exempt Mold Cleaner

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Cleaner.

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.

430 Wheeling Road Wheeling, IL 60090

Initial Supplier Identifier: THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN

ADDRESS IS USED

PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY

SDS Revision Date: 10/17/2024

COMPLIANT SDS FILE

Emergency

24 hour Emergency Emergency Telephone INFOTRAC 1-352-323-3500 (International)

Telephone No. 1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220

Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May displace oxygen and cause rapid suffocation.



Label elements







SDS Revision Date: 10/17/2024

Danger

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness and dizziness.

May displace oxygen and cause rapid suffocation.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Avoid breathing dust, fume, gas, mist, vapours, spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, eye protection, and face protection.

[Response]:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER, doctor or physician if you feel unwell.

If eye irritation persists: Get medical advice or attention.

Leaking gas fire - do not extinguish unless leak can be stopped safely.

In case of leakage, eliminate all ignition sources.

[Storage]:

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Store in a well ventilated place.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.



Section 3. Composition/information on ingredients

SDS Revision Date: 10/17/2024

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone	70-80	Flam. Liq. 2;H225	
CAS Number: 67-64-1		Eye Irrit. 2;H319	
Synonyms: 2-Propanone		STOT SE 3;H336	
1,1-Difluoroethane	20-35	Flam. Gas 1;H220	
CAS Number: 75-37-6		Liquified Gas;H280	
Synonyms: 1,1-difluoroethane (HFC-152A)		STOT SE 3;H336	
		Simple Asphyxiant	

The actual concentration or concentration range is withheld as a trade secret.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position and

obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart

and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.

Most important symptoms and effects, both acute and delayed

Overview No specific symptom data available.

Treat symptomatically. See section 2 for further details.

Eyes Causes serious eye irritation.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



Section 5. Fire-fighting measures

SDS Revision Date: 10/17/2024

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available. Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.



Section 7. Handling and storage

SDS Revision Date: 10/17/2024

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: No available information See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value		
67-64-1	Acetone	ACGIH	250 ppm 500 ppm		
		Alberta	500 ppm TWA; 1200 mg/m³TWA 750 ppm STEL; 1800 mg/m³STEL		
		British Columbia	250 ppm TWA 500 ppm STEL		
		Manitoba	250 ppm TWA 500 ppm STEL		
		New Brunswick	500 ppm TWA; 1188 mg/m³TWA 750 ppm STEL; 1782 mg/m³STEL		
		Newfoundland and Labrador	250 ppm TWA 500 ppm STEL		
		Nova Scotia	250 ppm TWA 500 ppm STEL		
		Northwest Territories	500 ppm TWA 750 ppm STEL		
		Nunavut	500 ppm TWA 750 ppm STEL		
		Ontario	250 ppm TWA 500 ppm STEL		
		Prince Edward Island	250 ppm TWA 500 ppm STEL		
		Quebec	500 ppm TWAEV; 1190 mg/m³TWAEV 1000 ppm STEV; 2380 mg/m³ STEV		
		Saskatchewan	500 ppm TWA 750 ppm STEL		
		Yukon	1000 ppm TWA; 2400 mg/m³TWA 1250 ppm STEL; 3000 mg/m³ STEL		
75-37-6	1,1-Difluoroethane	ACGIH	No Established Limit		
		Alberta	No Established Limit		
		British Columbia	No Established Limit		
		Manitoba	No Established Limit		
		New Brunswick	No Established Limit		
		Newfoundland and Labrador	No Established Limit		
		Nova Scotia	No Established Limit		
		Northwest Territories	No Established Limit		
		Nunavut	No Established Limit		
		Ontario	No Established Limit		
		Prince Edward Island	No Established Limit		
		Quebec	No Established Limit		
		Saskatchewan	No Established Limit		
		Yukon	No Established Limit		



Exposure controls

If workers are exposed to concentrations above the exposure limit they must use Respiratory

the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering **Controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

SDS Revision Date: 10/17/2024

Practices

Other Work Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly

before reuse.

See section 2 for further details.



Section 9. Physical and chemical properties

Physical State Pressurized aerosol dispensed as a mist.

Appearance

Odour

No available information

Melting point / freezing point No available information

Initial boiling point and boiling range $56.1 \,^{\circ}\text{C} / 133 \,^{\circ}\text{F}$ Flash Point $56.1 \,^{\circ}\text{C} / -4 \,^{\circ}\text{F}$

Evapouration rate (Ether = 1)No available information **Flammability (solid, gas)**Extremely flammable gas.

Upper/lower flammability or explosive limits Lower Explosive Limit: No available

information

Upper Explosive Limit: No available

SDS Revision Date: 10/17/2024

information

Vapour pressure (Pa)No available informationVapour DensityNo available informationRelative DensityNo available informationSolubility in WaterNo available information

Partition coefficient n-octanol/water (Log No available information

Kow)

Auto-ignition temperatureNo available informationDecomposition temperatureNo available informationViscosity (cSt)No available informationOxidising propertiesNo available informationExplosive propertiesNo available information

Other information

No other relevant information.



Section 10. Stability and reactivity

SDS Revision Date: 10/17/2024

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Avoid high temperatures and contact with incompatible material

Incompatible materials

No available information

Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
1,1-Difluoroethane - (75-37-6)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}



Carcinogen Data

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4
75-37-6	1,1-Difluoroethane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

SDS Revision Date: 10/17/2024

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

No specific symptom data available.

Treat symptomatically.

Eyes Causes serious eye irritation.



Section 12. Ecological information

SDS Revision Date: 10/17/2024

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Acetone - (67-64-1)	{CalcFish}	{CalcCrust}	{CalcAlgae}
1,1-Difluoroethane - (75-37-6)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

SDS Revision Date: 10/17/2024

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1950	UN1950	UN1950
UN proper	Aerosols	Aerosols, flammable	Aerosols,
shipping name			flammable
Transport hazard	TDG Hazard Class:2.1	IMDG:2.1	Air Class:2.1
class(es)	Sub Class:Not Applicable	Sub Class:Not Applicable	Sub Class:Not
			Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

1,1-Difluoroethane

Acetone

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Section 16. Other information

SDS Revision Date: 10/17/2024

SDS Revision Date 10/17/2024

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection B

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document