

Section 1. Identification

1.1. Product identifier 549BULK

Product Identity

Slide Bulk Heavy Duty 10% Mold Release
Alternate Names

Slide Bulk Heavy Duty 10% Mold Release
(SDS applies to pint, 1G, 5G, and 55G sizes)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Industrial Mold Release

1.3. Details of the supplier of the safety data sheet

Company Name Slide Products Inc.

430 Wheeling Road Wheeling, IL 60090

Emergency

24 hour Emergency Telephone Emergency Telephone INFOTRAC 1-352-323-3500

No. (International)

1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220

Fax: 1-847-541-7986

Section 2. Hazard(s) identification

2.1. Classification of the substance or mixture

Causes serious eye irritation.



2.2. Label elements





Warning

Causes serious eye irritation.

May cause drowsiness and dizziness.

[Prevention]:

Keep container tightly closed.

Avoid breathing dust, fume, gas, mist, vapors, spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, eye protection, and face protection.

[Response]:

IF INHALED: Remove victim to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER, doctor or physician if you feel unwell.

If eye irritation persists: Get medical advice or attention.

[Storage]:

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Isopropyl Alcohol CAS Number: 67-63-0	85 - 99	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
Polypropylene glycol, monobutyl ether CAS Number: 9003-13-8	4 - 15	Not Classified	

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position and

obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart

and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.



4.2. Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

Eyes Causes serious eye irritation.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available. Keep container tightly closed. Avoid breathing dust, fume, gas, mist, vapors, spray.

5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.



Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage. Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: No available information

Check section 2.2 (GHS Label Floments) for further of

Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

7.3. Specific end use(s)

No available information



Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value	
67-63-0	Isopropyl Alcohol	OSHA	TWA 400 ppm (980 mg/m ³) STEL 500 ppm	
		ACGIH	200 ppm 400 ppm	
		NIOSH	TWA 400 ppm (980 mg/m³) STEL: 500 ppm (1225 mg/m³)	
9003-13-8	Polypropylene glycol, monobutyl ether	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use

the appropriate, certified respirators.

Eyes Wear safety glasses with side shields to protect the eyes. An eye wash station is

suggested as a good workplace practice.

Skin Avoid skin contact. Protective gloves recommended.

Engineering Provide adequate ventilation. Where reasonably practicable this should be

Controls achieved by the use of local exhaust ventilation and good general extraction. If

these are not sufficient to maintain concentrations of particulates and any vapor

below occupational exposure limits suitable respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking,

Practices smoking or using toilet. Promptly remove soiled clothing and wash thoroughly

before reuse.

Check section 2.2 (GHS Label Elements) for further details.



Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State

Color

Odor

Odor threshold

рΗ

Melting point / freezing point

Initial boiling point and boiling range

Flash Point

Evaporation rate (Ether = 1) Flammability (solid, gas)

Upper/lower flammability or explosive limits

Vapor pressure (Pa)

Vapor Density Relative Density Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature Decomposition temperature

Viscosity (cSt) VOC Content

Oxidising properties Explosive properties Water Solubility

9.2. Other information

No other relevant information.

Liquid Pale tan

No available information No available information No available information

<-67.8 °C / <-90 °F

39.4-40.6 °C / 103-105 °F

11.7 °C / 53 °F > 1.7 Minutes

No available information **Lower Explosive Limit:** 1.0 % **Upper Explosive Limit:** 10.0 % 350 mm Hg @ 21 °C (70 °F)

>1 (Air=1) 0.791 (Water=1)

No available information No available information No available information No available information No available information

96%

No available information No available information

Nil



Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No available information

10.4. Conditions to avoid

Avoid high temperatures and contact with incompatible material

10.5. Incompatible materials

No available information

10.6. Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
lsopropyl Alcohol - (67-63-0)	5,840.00, Rat -	16,400.00, Rabbit -	72.60, Rat -	No data	No data
	Category: NA	Category: NA	Category: NA	available.	available.



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Polypropylene glycol, monobutyl ether - (9003-13-8)	9,100.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes;
		ACGIH	A4
9003-13-8	Polypropylene glycol, monobutyl ether	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable



Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	No data available.	No data available.
Polypropylene glycol, monobutyl ether - (9003-13-8)	104.00, Fish	101.00, Daphnia magna	122.00, Algae

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

No available information

12.4. Mobility in soil

No available information

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No available information

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	DOT (Domestic Surface	IMO / IMDG (Ocean	ICAO/IATA
	Transportation)	Transportation)	
14.1. UN number	UN1219	UN1219	UN1219
14.2. UN proper shipping name	Isopropyl alcohol solution	Isopropyl alcohol solution	Isopropyl alcohol solution
14.3. Transport	DOT Hazard Class: 3	IMDG:3	Air Class:3
hazard class(es)	Sub Class:Not Applicable	Sub Class:Not Applicable	Sub Class: Not Applicable
14.4. Packing group	II	II	II

14.5. Environmental hazards

Marine Pollutant: No;

14.6. Special precautions for user

No available information



Safety Data Sheet SDS Revision Date: 07/17/2024

Slide Bulk Heavy Duty 10% Mold Release

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive,

only selected regulations are represented.

Toxic Substance Control All components of this material are either listed or exempt from listing

Act (TSCA) on the TSCA Inventory.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Isopropyl Alcohol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



Section 16. Other information

SDS Revision Date	07/17/2024
SDS Revision Date	0//1//20/4

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards 0	Personal Protection G

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document