



Section 1. Identification

Product identifier 549BULK

Product Identity Slide Bulk Heavy Duty 10% Mold Release

Other means of identification Slide Bulk Heavy Duty 10% Mold Release
(SDS applies to pint, 1G, 5G, and 55G sizes)

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Release

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.
430 Wheeling Road
Wheeling, IL 60090

Emergency

24 hour Emergency Telephone No. Emergency Telephone INFOTRAC 1-352-323-3500
(International)
1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220
Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture

Eye Irrit. 2;H319 Causes serious eye irritation.
{PCField5d} May cause drowsiness or dizziness.

Label elements**Warning**

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

[Prevention]:

P233 Keep container tightly closed.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, and face protection.

[Response]:

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P337+313 If eye irritation persists: Get medical advice or attention.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the NOM-018-STPS-2015 Regulation.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Isopropyl Alcohol CAS Number: 67-63-0	85 - 99	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Polypropylene glycol, monobutyl ether CAS Number: 9003-13-8	4 - 5	Not Classified	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.
 Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Eyes Causes serious eye irritation.

Section 5. Fire-fighting measures**Extinguishing media**

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.
Keep container tightly closed.
Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

Section 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage**Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: No available information
See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	ACGIH	200 ppm 400 ppm
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	200 ppm TWA VLE-PPT 400 ppm STEL [PPT-CT]
9003-13-8	Polypropylene glycol, monobutyl ether	ACGIH	No Established Limit
		DNEL Local Exposure	No Established Limit
		DNEL Systematic Exposure	No Established Limit
		National	No Established Limit

Exposure controls

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.
- Skin** Avoid skin contact. Protective gloves recommended.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	Pale tan Liquid
Odour	No available information
Odour threshold	No available information
pH	No available information
Melting point / freezing point	<-67.8 °C / <-90 °F
Initial boiling point and boiling range	39.4-40.6 °C / 103-105 °F
Flash Point	11.7 °C / 53 °F
Evapouration rate (Ether = 1)	> 1.7 Minutes
Flammability (solid, gas)	No available information
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.0 % Upper Explosive Limit: 10.0 %
Vapour pressure (Pa)	350 mm Hg @ 21 °C (70 °F)
Vapour Density	>1 (Air=1)
Relative Density	0.791 (Water=1)
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log Kow)	No available information
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
VOC Content	96%
Oxidising properties	No available information
Explosive properties	No available information
Water Solubility	Nil
 Other information	
No other relevant information.	

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Avoid high temperatures and contact with incompatible material

Incompatible materials

No available information

Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Isopropyl Alcohol - (67-63-0)	5,840.00, Rat - Category: NA	16,400.00, Rabbit - Category: NA	72.60, Rat - Category: NA	No data available.	No data available.



Safety Data Sheet
Slide Bulk Heavy Duty 10% Mold Release

SDS Revision Date: 07/17/2024

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Polypropylene glycol, monobutyl ether - (9003-13-8)	9,100.00, Rat - Category: NA	>2,000.00, Rabbit - Category: 5	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	A4
9003-13-8	Polypropylene glycol, monobutyl ether	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Symptoms and effects, both acute and delayed::

Treat symptomatically.

Eyes Causes serious eye irritation.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Isopropyl Alcohol - (67-63-0)	10,000.00, Pimephales promelas	No data available.	No data available.
Polypropylene glycol, monobutyl ether - (9003-13-8)	104.00, Fish	101.00, Daphnia magna	122.00, Algae

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	SCT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1219	UN1219	UN1219
UN proper shipping name	Isopropyl alcohol solution	Isopropyl alcohol solution	Isopropyl alcohol solution
Transport hazard class(es)	DOT Hazard Class:3 Sub Class:Not Applicable	IMDG:3 Sub Class:Not Applicable	Air Class:3 Sub Class:Not Applicable
Packing group	II	II	II

Environmental hazards

Marine Pollutant: No;

Special precautions for user

No available information



Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria of NOM-018-STPS-2015 and the SDS contains the information required by those regulations.

Mexico - National Inventory of Chemical Substances (INSQ):

Isopropyl Alcohol



Section 16. Other information

SDS Revision Date 07/17/2024

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards 2	Flammability 3	Physical Hazards 0	Personal Protection G

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document