SLIDE.

TECHNICAL DATA SHEET



PAINTABLE MOLD RELEASE

Safe for use with all plastics Seguro para ser usado con todos los plásticos

Use where parts must be painted, hot stamped or metalized Para uso en partes que tienen que pintárse, estampárse al calor o metalizárce



Paintable Mold Release Aerosol 40012N

Product Description

This Paintable Mold Release is UL recognized and requires no special cleaning. It will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating operations. You get perfect finishes every time and more cycles per can over other comparable releases. Extremely effective for investment wax casting, injection and compression molding.

Applications	Mold Release
Unit Package Description	16 ounce aerosol
Generic Description	Paintable Mold Release
Net Weight Fill	11.5 net ounces
UPC Code	858799000004
Appearance	Clear Oily Colorless Liquid
Odor	Ether like
Flash Point F	Not Applicable
Flash Point C	Not Applicable
Base Type	Paintable Silicone Fluid
Evaporation Rate	Fast
HMIS Rating	1, 3, 0, B
DOT Proper Shipping Name	UN 1950, Aerosols, Flammable, 2.1, Limited Quantity
VOC % (Federal)	60
VOC g/L (Federal)	441.96
VOC lbs./Gal (Federal)	3.68
Removal	Remove with organic or hydrocarbon solvents
Units Per Case	12
Case Weight (Ibs)	13
Working Temperature F	32 to 650 degrees
Working Temperature C	0 to 343 degrees
Propellant	DME/152A
NFPA Aerosol Flammability Level	1
Independent Certifications	UL recognized



1-800-323-6433 • www.SlideProducts.com