

TECHNICAL DATA SHEET





Econo-Spray® 3 Mold Release Aerosol 40810P

Product Description

Econo-Spray® 3 contains a highly effective non-silicone release in a non-chlorinated solvent carrier system. This product is highly paintable, and will permit ultrasonic welding of molded parts. It affords excellent release of all thermoplastics.

Applications Mold Release

Unit Package Description 16 ounce aerosol

Generic Description Paintable Mold Release

Net Weight Fill 10 net ounces
UPC Code 858799000080

Appearance Clear Oily Colorless Liquid

Odor Mild, Petroleum like

Flash Point F Not Applicable

Flash Point C Not Applicable

Base Type Propylene Glycol

Evaporation Rate Fast

HMIS Rating 1, 4, 0, B

DOT Proper Shipping Name UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal) 97
VOC g/L (Federal) 613

VOC lbs./Gal (Federal) 5.12

Removal Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR) 21CFR 178.3570

Units Per Case 12

Case Weight (lbs) 12

Working Temperature F 32 to 600 degrees

Working Temperature C 0 to 315 degrees

Propellant Propane

NFPA Aerosol Flammability Level 3