

TECHNICAL DATA SHEET



Econo-Spray® 3 Mold Release Aerosol

40810P

Product Description

Econo-Spray® 3 contains a highly effective non-silicone release in a non-chlorinated solvent carrier system. This product is highly paintable, and will permit ultrasonic welding of molded parts. It affords excellent release of all thermoplastics.

Applications

Mold Release

Shelf Life

Three years from Date of Manufacture (as found on the bottom of each can and shipping box)

Unit Package Description

16 ounce aerosol

Generic Description

Paintable Mold Release

Net Weight Fill

10 net ounces

UPC Code

858799000080

Appearance

Clear Oily Colorless Liquid

Odor

Mild, Petroleum like

Flash Point F

Not Applicable

Flash Point C

Not Applicable

Base Type

Propylene Glycol

Evaporation Rate

Fast

HMIS Rating

1, 4, 0, B

DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal)

97

VOC g/L (Federal)

613

VOC lbs./Gal (Federal)

5.12

Removal

Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR)

21CFR 178.3570

Units Per Case

12

Case Weight (lbs)

12

Working Temperature F

32 to 600 degrees

Working Temperature C

0 to 315 degrees

Propellant

Propane

NFPA Aerosol Flammability Level

3