


## TECHNICAL DATA SHEET



### Super Grease Non-Aerosol

43900-01, 43900-03, 43900T, 43900-7, 43900-35,  
43900-400

#### Product Description

Super Grease will not separate, run or fall out and has exceptional load-bearing properties. Thixotropic properties provide excellent mechanical stability when sudden temperature changes occur. A clear, clean, non-yellowing grease, Super Grease is ideal for injection molds, mold assemblies, and especially medical and food grade plastic parts. It also repels water and prevents corrosion.

#### Applications

Ejector Pin Lubricant

#### Unit Package Description

Multiple sizes

#### Generic Description

Ejector Pin Grease

#### Net Weight Fill

multiple sizes

#### UPC Code

858799000752

#### Appearance

Colorless Grease

#### Odor

None

#### Flash Point F

455 degrees

#### Flash Point C

235 degrees

#### Base Type

PTFE

#### Evaporation Rate

N/A

#### HMIS Rating

0, 1, 0 , None Determined

#### DOT Proper Shipping Name

Not Regulated, Lubricating, NOI

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

NSF H1

#### Units Per Case

multiple sizes

#### Working Temperature F

-45 to 650 degrees

#### Working Temperature C

-43 to 343 degrees

#### Propellant

N/A

#### NFPA Aerosol Flammability Level

N/A

#### Independent Certifications

NSF category H1