

## TECHNICAL DATA SHEET





## **Urethane Mold Release Aerosol** 45812H

## **Product Description**

Urethane mold release is extremely effective for all polyurethanes: rigid, semi-rigid and flexible urethane foams. Urethane mold release imparts a light, dry coating on the mold, eliminating build-up. Yet, it is so effective that it continues to work for several cycles between applications. Non-paintable formulation.

Applications Mold Release

Unit Package Description 16 ounce aerosol

Generic Description Mold Release for Urethane Resins

Net Weight Fill 11.5 net ounces

**UPC Code** 858799000585

Appearance Clear Oily Colorless Liquid

Odor Ether like

Flash Point F Not Applicable

Flash Point C Not Applicable

Base Type Silicone

**Evaporation Rate** Fast

**HMIS Rating** 1, 3, 0, B

**DOT Proper Shipping Name** UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

**VOC % (Federal)** 57.78

VOC g/L (Federal) 431.97

VOC lbs./Gal (Federal) 3.6

Removal Remove with organic or hydrocarbon solvents

Units Per Case 12

Case Weight (lbs) 13

Working Temperature F 32 to 500 degrees

Working Temperature C 0 to 260 degrees

Propellant DME/152A

NFPA Aerosol Flammability Level 1